

TITLE OF THE INVENTION

PACKET TRANSFER COMMUNICATION APPARATUS, PACKET  
TRANSFER COMMUNICATION METHOD, AND STORAGE MEDIUM

CROSS-REFERENCE TO RELATED APPLICATIONS

5           This is a Continuation Application of PCT  
Application No. PCT/JP00/09330, filed December 27,  
2000, which was not published under PCT Article 21(2)  
in English.

10           This application is based upon and claims the  
benefit of priority from the prior Japanese Patent  
Application No. 11-375682, filed December 28, 1999,  
the entire contents of which are incorporated herein  
by reference.

BACKGROUND OF THE INVENTION

15           1. Field of the Invention

          This invention relates to a packet transfer  
communication apparatus, a packet transfer  
communication method, and a storing medium, and more  
particularly to a packet transfer communication  
20   apparatus, a packet transfer communication method, and  
a storage medium which transferring audio data, video  
data, and the like using a packet switching network.

2. Description of the Related Art

          Real-Time Transport Protocol (hereinafter,  
25   referred to as RTP) have been determined as  
communication protocols used to transfer data which  
real-time response is important, such as audio data and

video data, through a packet switching network, such as the Internet.

As underlying protocols of RTP, that is, protocols in the transport layer, there are User Datagram  
5 Protocol (hereinafter, referred to as UDP) and Internet Protocol (hereinafter, referred to as IP).

UDP and IP are connectionless communication protocols where no logical setting is done between peer-to-peer. Since they are best-effort-type  
10 protocols that do not guarantee the communication transmission, when the network is crowded, they are considered to be unreliable. That is, neither UDP nor IP is considered to have the function of securing the reliability of communication.

15 Since the packets transmitted according to RTP from the packet transfer communication apparatus on the transmission side are communicated using the aforementioned UDP and IP, a problem arises: the order of delivery of packets sequentially transmitted over  
20 the packet switching network might change or some packets might be lost while these are transmitted. For instance, when packet switching networks are connected with some routers, each packet sequentially transmitted takes a different packet transmission path. When they  
25 are received by the packet transfer communication apparatus on the reception side, the order of delivery of packets might change or some packets might be lost

during transmission over the packet switching networks.

RTP has been defined by Internet Engineering Task Force and the RTP packet format and Real-Time Control Protocol (hereinafter, referred to as RTCP) are  
5 specified in the RTP specification. An RTP packet is composed of an RTP header and an RTP payload. The RTP header is made up of fields, including a sequence number field, a time stamp field, a payload type field and so on. The RTP payload corresponds to a field for  
10 storing data whose real-time response is important, including audio and video data to be transmitted.

Normally, the packet transfer communication apparatus on the transmission side gives numerical values to the sequence number field of the RTP headers  
15 consecutively in the order in which the packets are to be transmitted, thereby transmitting the packets. The packet transfer communication apparatus on the reception side refers to the sequence number fields of the RTP headers of the received packets. If the  
20 sequence numbers are not consecutive, the apparatus judges that some packet is missing or the order of the packets have been changed.

Since a real-time response is regarded as important in the data transmitted in RTP as described  
25 above, the packets consecutively received are treated as valid data. The packets whose order was changed in transmission are judged to have been partially lost or

changed in their order when the packet transfer communication apparatus on the reception side failed to receive the packets consecutively. Then, they are treated as invalid data and discarded.

5           For this reason, in a case where the packets have been transferred with their order changed, since the packet transfer communication apparatus on the reception side discard the data as invalid data in it, even though the data has arrived at the reception-side  
10           apparatus, the quality of communication might deteriorate seriously, although the real-time response feature is not deteriorating in composing the data.

          As described above, in a case where the order of packets have been changed when the data whose real-time  
15           response is important, such as audio data and video data, has been transferred according to RTP through a packet switching network and received by the packet transfer communication apparatus on the reception side, the following problem arises: although the real-time  
20           response feature is not deteriorating in composing the data, the quality of communication deteriorates, because the data is discarded as invalid data, even though the data has reached the packet transfer communication apparatus on the reception side.

25                           BRIEF SUMMARY OF THE INVENTION

          The object of the present invention is to provide a packet transfer communication apparatus, a packet

transfer communication method, and a storage medium  
which are capable of not only composing the data in  
real time even when the order of delivery of packets  
have been changed but also improving the quality of  
5 communication.

According to the present invention, there is  
provided a communication apparatus which is connected  
to a communication network and, via the communication  
network, communicates packets including sequence  
10 numbers and data to be transmitted, the packet transfer  
communication apparatus comprising:

reception means for receiving packets from the  
communication network;

15 extraction means for extracting the sequence  
numbers and the data to be transmitted from the packets  
received by the reception means, in such a manner that  
the sequence numbers are consecutive or discontinuous;

storage means for storing the sequence number of  
the packet until the packet whose sequence number lies  
20 between the discontinuous sequence numbers have been  
received, or during a specific period of time; and

rearrangement means for rearranging the received  
data including the data in the newly received packet  
and the data in the previously received packets on the  
25 basis of the sequence number of the new packet  
extracted by the extraction means and the sequence  
numbers stored in the storage means.

Furthermore, according to the present invention,  
there is provided a packet transfer communication  
method in a packet transfer communication apparatus  
which is connected to a communication network and,  
5 via the communication network, communicates packets  
including sequence numbers and data to be transmitted,  
the packet transfer communication method comprising:

the step of receiving packets from the  
communication network;

10 the step of extracting the sequence numbers and  
the data to be transmitted from the packets received in  
the receiving step, in such a manner that the sequence  
numbers are consecutive or discontinuous;

the step of storing the sequence number of the  
15 packet until the packet whose sequence number lies  
between the discontinuous sequence numbers have been  
received, or during a specific period of time; and

a rearrangement step of rearranging the received  
data including the data in the newly received packet  
20 and the data in the previously received packets on  
the basis of the sequence number of the new packet  
extracted in the extracting step and the sequence  
number stored in the storing step.

Still furthermore, according to the present  
25 invention, there is provided a storage medium which  
stores a program for operating a packet transfer  
communication apparatus or a computer connected to

a communication network, the storage medium

causing the packet transfer communication apparatus or computer to receive packets from the communication network,

5 causing the data to be transmitted and the sequence numbers given to the packets in packet transmission to be extracted consecutively or discontinuously from the received packet,

causing the sequence number of the packet until  
10 the packet whose sequence number lies between the discontinuous sequence numbers have been received or during a specific period of time, and

storing a program for rearranging the received data including the data in the newly received packet  
15 and the data in the previously received packets on the basis of the sequence number of the newly extracted packet and the stored sequence numbers, in such a manner that the packet transfer communication apparatus or computer can read the program.

20 With the present invention, in the packet transfer communication apparatus on the reception side, the storage means stores the sequence numbers of the packets received within a specific period of time until the reception means has received a new packet. Then,  
25 after the reception means has received a new packet, the sequence number given to the packet in packet transmission and the data to be transmitted are

extracted from the packet. On the basis of the  
sequence number of the extracted new packet and the  
sequence number in the storage means, the received data  
including the data in the packet just received is  
5 rearranged. This prevents the data from being lost  
even when the order of arrival of packets have been  
changed, which improves the quality of communication.

According to the present invention, there is  
provided a packet transfer communication apparatus,  
10 wherein the rearrangement means includes

means for comparing the sequence number extracted  
by the extraction means with the sequence numbers  
stored in the storage means and thereby judging whether  
the order in which the packets were received is correct  
15 or not,

means for, if the result of the comparison showed  
that the order in which the packets were received is  
incorrect, forming a list of the sequence numbers of  
the packets likely to be received in future, and

20 means for, when the reception means has received a  
new packet within a specific period of time, inserting  
new data having a sequence number in the list into a  
suitable position so that the new data may be arranged  
in the stream of the received data in the order of  
25 sequence numbers.

Therefore, the packet transfer communication  
apparatus on the reception side judges from the



sequence number set in the received packet whether the order in which the packets were received and the order in which the transmission side transmitted the packets are correct or not and causes the timer to operate from this point in time until a specific time. If the order of packets on the transmission side differs from that on the reception side, a list of the sequence numbers expected to arrive and packets are waited for. Then, when a packet corresponding to a sequence number in the list is received within a specific period of time, the data is inserted into a suitable position in the data.

Furthermore, according to the present invention, there is provided a packet transfer communication apparatus comprising means for deleting the corresponding sequence number from the list after the specific period of time has elapsed.

Therefore, after a list of the sequence numbers of the packets expected to arrive is formed, the timer is operated. When the timer reaches time out after a specific time has elapsed, the corresponding sequence number is deleted from the list. As a result, the packet with the sequence number is treated as a missing packet, which makes it possible to compose the data without a further delay.

Specifically, with the present invention, even if the order of arrival of packets have been changed when the packet transfer communication apparatus on the

reception side has received packets, the packet  
expected to arrive is awaited for a specific period of  
time. If the packet has arrived within the specific  
period of time, the packets are rearranged in the  
5 correct order of packets, which improves the quality of  
communication.

If the packet expected to arrive has not received  
within the specific period of time, the packet is  
treated as a missing packet as usual and the data is  
10 composed from the existing received data stream, which  
prevents the real-time response feature from being  
lost.

As a result, even when the order of arrival of  
packets have been changed, the data can be composed  
15 without losing the real-time feature and moreover the  
quality of communication can be improved.

Additional objects and advantages of the invention  
will be set forth in the description which follows, and  
in part will be obvious from the description, or may  
20 be learned by practice of the invention. The objects  
and advantages of the invention may be realized and  
obtained by means of the instrumentalities and  
combinations particularly pointed out hereinafter.

#### BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

25 The accompanying drawings, which are incorporated  
in and constitute a part of the specification,  
illustrate embodiments of the invention, and together

with the general description given above and the detailed description of the embodiments given below, serve to explain the principles of the invention.

FIG. 1 is a block diagram schematically showing a packet transfer communication system according to an embodiment of the present invention;

FIG. 2 schematically shows a packet structure complying with RTP in the system shown in FIG. 1;

FIG. 3 is a table showing an example of writing in a list of the packet transfer communication system of FIG. 1;

FIG. 4 is a flowchart for the process of changing the order of packets in the packet transfer communication system of FIG. 1; and

FIG. 5 is a flowchart for the processing done when the timer has reached time out in the packet transfer communication system of FIG. 1.

#### DETAILED DESCRIPTION OF THE INVENTION

Hereinafter, referring to the accompanying drawings, a packet transfer communication system according to an embodiment of the present invention will be explained in detail.

FIG. 1 shows a packet transfer communication system according to an embodiment of the present invention.

In FIG. 1, reference numerals 1 and 2 indicate communication apparatuses. The communication apparatus

1 and communication apparatus 2 are connected to each other via a communication network 3. The communication network 3 is, for example, a packet switching network, such as the Internet, and may be operated via cables or by radio.

The communication apparatus 1 comprises a packetizer circuit 11 for converting data streams into packets, a counter for giving sequence numbers to the packets, a packet transmitting/receiving section 13 for transmitting and receiving packets, a packet reassembler circuit 14 for depacketizing the received packets, a reception buffer 15 for holding temporarily the data extracted from the received packets, a timer 16, a reception-expected packet list 17 (hereinafter, referred to as the list 17) in which a list of the packets which have not been received yet at a certain time and will possibly be received after that time is written together with their writing time, and an order rearranging section 18 for changing the order of data supplied to the reception buffer 15.

The communication apparatus 2, which has the same circuit configuration as that of the communication apparatus 1, comprises a packetizer circuit 21, a counter 22, a packet transmitting/receiving section 23, a packet reassembler circuit 24, a reception buffer 25, a timer 26, a reception-expected packet list 27 (hereinafter, referred to as the list 27), and an order

rearranging section 28.

IP packets complying with RTP, which are transmitted and received over the communication network 3 between the communication apparatuses 1 and 2, for example, a packet switching network, have a structure as shown in FIG. 2. As shown in FIG. 2, an IP packet is composed of an IP payload 5 and an IP header 4 added to the head of the IP payload 5. The IP payload 5, a UDP packet, is made up of a UDP payload 7 and a UDP header 6 added to the head of the UDP payload 7. Furthermore, the UDP payload 7, an RTP packet, is composed of an RTP payload 9 and an RTP header 8 added to the head of the RTP payload 9. The RTP header 8 is made up of fields, including a sequence number field, a time stamp field, a payload type field and so on. The RTP payload 9 corresponds to a field for storing data whose real-time response is important, such as audio data and video data to be transmitted.

In the packet transfer communication system for transmitting and receiving packets of such a structure, data streams to be transmitted, that is, data whose real-time response is important, such as video and audio data to be transmitted, are supplied to the packetizer circuits 11, 21. In the packetizer circuits 11, 21, the data streams are stored in the RTP payload 9 and the RTP header 8 is added as the information necessary to the RTP payload, thereby converting

the RTP payload into RTP packets as UDP payloads 7. The counters 12, 22 supply sequence numbers to the packetizer circuits 11, 21. The packetizer circuits 11, 21 count up each time an RTP packet is created, thereby generating a new sequence number. RTP packets, UDP payloads, composed of the RTP header 8 and RTP payload 9 are supplied to the packet transmitting/receiving sections 13, 23. In the packet transmitting/receiving sections 13, 23, the UDP header 6 is added to an RTP packet, a UDP payload 7, thereby converting the RTP packet into a UDP packet, an IP payload 5. To the UDP packet, the IP payload 5, the IP header is further added, thereby converting the UDP packet into an IP packet. The packet transmitting/receiving sections 13, 23 include a cable or radio communication interface or a cable and radio communication interface and transmit the IP packets created by the packetizer circuits 11, 21 to the communication network 3.

Furthermore, the packet transmitting/receiving sections 13, 23 receive IP packets from the communication network 3. In the packet transmitting/receiving sections 13, 23, the IP header 4, UDP header 6, and UDP payload 7, an RTP packet, are interpreted and cut out from the received packets. The UDP payload 7, an RTP packet, is supplied to the packet reassembler circuit 14. In the packet reassembler circuit 14, the UDP

payload 7 is separated into the RTP payload 9 and RTP header 8. The data stream in the RTP payload 9 is supplied via the order rearranging section 18 to the reception buffers 15, 25.

5           The reception buffers 15, 25 include buffers that enable the data to be outputted from the reception side in the order in which the transmission side transmitted the data. In a subsequent process, to process the data with an application, the data is taken out of the  
10           reception buffer 25 in the form of data streams and outputted. If the application is, for example, an Internet telephone program, the audio data can be received in real time. If the application is a teleconference program, video streams and audio streams  
15           can be composed in real time, thereby realizing teleconferences.

          When an RTP packet Sc is inputted, the order rearranging circuit 18 compares the sequence number of the sequence number of the RTP packet Sc with  
20           the sequence number of the RTP packet Sb inputted immediately before the input of the RTP packet Sc to the order rearranging circuit 18. If the sequence number of the RTP packet Sc follows the sequence number of the RTP packet Sb, the data in the RTP packet Sc is  
25           considered to follow the data in the RTP packet Sb and supplied to the reception buffer 15 in that order. If the sequence number of the RTP packet Sc is smaller

than the sequence number of the RTP packet Sb ( $S_c < S_b$ ), the RTP packet  $S_c$  is supplied to the reception buffers 15, 25 in such a manner that it is arranged before the RTP packet Sb. If the sequence number of the RTP packet  $S_c$  is bigger than the sequence number of the RTP packet Sb but does not follow the latter ( $S_c > S_b$  but  $S_c \neq S_b + 1$ ), it is considered that an RTP packet whose sequence number ( $S_b + 1$  to  $S_c - 1$ ) lies between the sequence number  $S_c$  of the RTP packet and the sequence number of the RTP packet Sb has not been received yet, the sequence numbers ( $S_b + 1$  to  $S_c - 1$ ) between them are written together with the writing time into the list 17. For instance, it is assumed that the sequence number of the RTP packet arrived earlier at the order rearranging circuit 18 is "11190" and the sequence number of the packet arrived later is "11200." In this case, it is considered that the packets whose sequence numbers ranging from "11191" to "11199" have not been received. Then, the sequence numbers ranging from "11191" to "11199" will possibly be received in future and written in the list.

In a case where the sequence number of the RTP packet  $S_c$  is smaller than the sequence number of the RTP packet ( $S_c < S_b$ ), if it has been verified that the sequence number of the RTP packet  $S_c$  is in the list, the number is deleted from the list and put in the row following the RTP packet Sb. After the sequence number



of the RTP packets are arranged in the reception buffers 15, 25 in a consecutive manner, the data in the RTP packets is supplied sequentially to the reception buffers 15, 25.

5           Hereinafter, in the packet transfer communication system, since the communication apparatus 1 and communication apparatus 2 have the same circuit configuration, a case where the data is transferred from the communication apparatus 1 to communication  
10           apparatus 2 will be explained as an example of the communicating operation to simplify the explanation given below. To do this, let the communication apparatus 1 be the transmission side and the communication apparatus 2 be the reception side.

15           On the transmission side, when the data stream to be transmitted is inputted, the data stream is transferred to the packetizer circuit 11.

            In the packetizer circuit 11, the data stream is divided at suitable intervals to determine RTP  
20           payloads. RTP headers are added to the RTP payloads, thereby converting the data stream into packets.

            In this way, RTP packets are created. In the sequence number field of the RTP header, the value read from the counter 12 is stored as the sequence number.

25           The counter 12 counts up each time an RTP packet is created at the packetizer circuit 11. The count value is outputted as the sequence number of the packet.

The RTP packet is sent to the packet transmitting/  
receiving section 13, which further adds a UDP header  
and an IP header, converting the RTP packet into an IP  
packet. The IP packet outputted from the packet  
5 transmitting/receiving section 13 is transmitted via  
the communication network 3 to the packet transmitting/  
receiving section 23 on the reception side, which  
receives the packet.

On the reception side, after the packet  
10 transmitting/receiving section 23 receives the IP  
packet, the IP packet is separated into the IP header,  
UDP header, and UDP payload. The UDP payload is sent  
to the packet reassembler circuit 24. In the packet  
reassembler circuit 24, the UDP payload is depacketed  
15 and separated into the RTP header and RTP payload.  
Then, the data is extracted from the RTP payload  
and the value Sc is extracted as a sequence number  
from the sequence number field of the RTP header.  
The data and the value Sc in the sequence number field  
20 of the RTP header extracted by the packet reassembler  
circuit 24 are transferred to the order rearranging  
section 28.

The operation in the order rearranging section 28  
of the communication apparatus 2 will be explained by  
25 reference to FIG. 3. FIG. 3 is a flowchart showing  
the process in the order rearranging section which  
rearranges the packets in the order in which they were

transmitted, when they have reached the communication apparatus 2 on the reception side in the packet transfer communication system.

As described above, in the communication apparatus  
5 2 on the reception side, when a packet has reached  
the packet reassembler circuit 24 and the sequence  
number field of the RTP header has been recognized,  
the packet reassembler circuit 24 hands over the  
data and sequence number  $S_c$  to the order rearranging  
10 section 28. Then, the order rearranging section 28  
refers to the handed-over sequence number  $S_c$  and the  
previously received sequence number  $S_b$  (the sequence  
number of the RTP packet previously arrived) and  
compares them ( $S_{101}$ ,  $S_{103}$  and  $S_{105}$ ). When the result  
15 of the comparison has shown that they are the same  
sequence number ( $S_c = S_b$ ) ( $Y$  in  $S_{101}$ ), the order  
rearranging section 28 judges that the newly received  
RTP packet is a repeated RTP packet and deletes  
the data from the reception buffer 25, or discards  
20 the data ( $S_{102}$ ).

When the result of the comparison has shown that  
the sequence number  $S_c$  is the number ( $S_c = S_b + 1$ )  
following the reference sequence number  $S_b$  ( $Y$  at  $S_{103}$ ),  
the order rearranging section 28 regards the sequence  
25 number  $S_b$  and sequence number  $S_c$  as consecutive RTP  
packets and stores the data on the sequence number  $S_c$   
in the area next to the area of the reception buffer 25

in which the sequence number Sb has been stored (S104).  
That is, the data on the sequence number Sc is stored  
in the area specified by the address following the  
address of the area in which sequence number Sb has  
5 been stored.

Furthermore, when the result of the comparison has  
shown that the sequence number Sc is smaller than the  
sequence number Sb ( $Sc < Sb$ ) (Y at S105), the order  
rearranging section 28 searches the list 27 of waiting  
10 packets for the sequence number Sc (S106).

If the sequence number Sc is not in the list 27 of  
waiting packets (N at S106), the order rearranging  
section 28 discards the packet having the sequence  
number Sc (S107).

15 When hitting the sequence number Sc as a result  
of searching the list 27 (Y at S106), the order  
rearranging section 28 deletes the corresponding  
sequence number from the list 27 (S108), cancels  
(or stops) the counting operation of the timer 26  
20 corresponding to the sequence number (S109), and  
inserts the data stream into a suitable storage area of  
the reception buffer 25 corresponding to the sequence  
number Sc (S110).

On the other hand, if the sequence number Sc is  
25 not smaller than the reference sequence number Sb in  
the comparing process at S105 (not  $Sc < Sb$ ) (N at  
S105), that is, if the sequence number Sc is larger

than the reference sequence number  $S_b$  ( $S_c > (S_c + 1)$ ),  
the order rearranging section 28 not only stores the  
packet with the sequence number  $S_c$  into the reception  
buffer 25 (S111) but also adds the sequence numbers  
5  $S_b + 1$  to  $S_c - 1$  to the waiting packet list 27 to wait  
for the RTP packets having the sequence numbers  $S_b + 1$   
to  $S_c - 1$  (S112). Then, the section 28 starts the  
counting operation of the timer 26 for the sequence  
number of each waiting packet (S113). The timer 26 may  
10 be formed by software or hardware. It is assumed that  
as many timers as the apparatus permits are provided.

FIG. 3 is a flowchart showing the processing when  
the timer 26 has reached time out.

As shown in FIG. 3, when a certain period of time  
15 has elapsed since the order rearranging section 28  
started the counting operation of the timer 26 and  
the time 26 has reached time out (S201), the order  
rearranging section 28 searches for the sequence number  
related to the timer 26 (S202).

20 When the sequence number has been found as  
a result of the search (Y at S202), the sequence  
number is deleted from the waiting list 27 (S203)  
and the packet is treated as a missing packet.  
Then, the order rearranging section 28 terminates  
25 the process.

Furthermore, when the sequence number has not been  
found as a result of the search (N at S202), the order

rearranging section 28 terminates the process as it is.

It is assumed that the user can set arbitrarily the time required for the timer 26 to reach time out.

As described above, with the packet transfer  
5 communication system according to the embodiment, when  
an IP packet arrived at the communication apparatus 2  
on the reception side and the sequence number field  
in the RTP header has been recognized, the packet  
reassembler circuit 24 hands over the data and sequence  
10 number Sc to the order rearranging section 28. The  
order rearranging section 28 compares the handed-over  
sequence number Sc with the sequence number Sb (the one  
previously arrived) already stored in the reception  
buffer 25. According to the result of the comparison,  
15 the received data and the data in the reception buffer  
25 are rearranged. This makes it possible to compose  
the data without losing the real-time response feature  
and further improve the quality of communication, even  
when the order of arrival of IP packets have been  
20 changed.

Furthermore, when packets are received by the  
communication apparatus 2, the time required for the  
timer 26 to reach time out can be set arbitrarily.  
This makes it possible to rearrange the received  
25 packets in the order of transmission, while keeping the  
delay time necessary for the application.

That is, even when the order of arrival of packets

have been changed, it is possible to rearrange the packets in the proper order of the packets without discarding packets, requesting retransmission, or losing the real-time response feature.

5           The present invention is not limited to the above embodiment.

10           In the embodiment, the communication apparatus 1 has transmitted packets and the communication apparatus 2 has received them. Since the communication apparatus 1 and the communication apparatus 2 have the same configuration, the latter may transmit packets and the former receive them.

15           While in the embodiment, each of the communication apparatuses 1, 2 has been composed of the packetizer circuit, counter, packet transmitting/receiving section, packer reassembler circuit, reception buffer, timer, and reception-expected packet list, these component parts may be realized in software.

20           The software may be stored onto a storage medium from which a computer or a portable communication terminal can read the data, such as a floppy disk or a flash memory. In this case, a computer or a portable communication terminal reads the software (programs) stored on a storage medium, thereby enabling the  
25           processes in each embodiment.

          The storage medium may be not only a floppy disk or a flash memory but also a magnetic disk, a hard

disk, an optical disk (such as CD-ROM, CD-R, or DVD),  
a magneto-optical disk (such as MO), or a semiconductor  
memory. That is, the storage medium may use any  
storing method, provided that it can store programs and  
5 enables a computer to read the data from it.

Furthermore, under the control of the program  
installed from a storage medium into the computer, the  
OS (operating system) or the MW (middleware), such as  
a database management application program or a network  
10 application program, running on the computer may  
execute part of each process for realizing the  
embodiment.

The storage medium is not restricted to a medium  
independent of the computer and may be a storage medium  
15 into which a program transmitted over a LAN or the  
Internet has been downloaded and stored or permanently  
stored.

Furthermore, the number of storage mediums is not  
limited to one. A plurality of storage mediums may  
20 be used in executing the processes in the embodiment.  
In this case, too, the storage mediums are included in  
the scope of storage medium in the present invention.  
Each medium may take any configuration.

The computer, which executes each process in the  
25 embodiment under the control of the program stored on  
the storage medium, may be composed of a single  
personal computer or a system made up of units



connected to form a network.

In addition, the computer is not limited to  
a personal computer and may be an arithmetic operation  
unit or a microcomputer included in an information  
5 processing unit. The units and apparatuses capable of  
realizing the function of the present invention using  
programs are generically called the computer.

As described above, with the present invention,  
the storage means stores the sequence numbers of the  
10 packets received within a specific period of time until  
the reception means have received a new packet in  
the packet transfer communication apparatus on the  
reception side. When the reception means has received  
a new packet, the sequence number given to the packet  
15 in packet transmission and the data to be transmitted  
are extracted from the packet. On the basis of the  
sequence number of the extracted new packet and the  
sequence number in the storage means, the received data  
including the data in the just received packet are  
20 rearranged. Therefore, even when the order of arrival  
of packets have been changed, part of the data stream  
is prevented from being lost, which improves the  
quality of communication.

With the present invention, the packet transfer  
25 communication apparatus on the reception side judges  
from the sequence numbers set in the received packets  
whether the order in which the packets were received

and the order in which the transmission side transmitted the packets are correct or not. When the order of the packets on the transmission side and that on the reception side are incorrect, a list of the sequence numbers expected to arrive is formed and the packets are waited for. Then, when a packet corresponding to a sequence number in the list is received within a specific period of time, the data is inserted in a suitable data position in the data.

Furthermore, with the present invention, since the corresponding sequence number is deleted from the list after a specific time has elapsed, the packet with the sequence number is treated as a missing packet, which enables the data to be composed without a further delay.

As a result, even when the order of arrival of packets have been changed, the data can be composed without losing the real-time response feature, and moreover, the quality of communication can be improved.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.